

3380 Series Commercial Fan Forced Ceiling Heater

Product Specifications

The heaters are be constructed of a heavy gauge steel housing. The rough-in dimensions are 19 3/16" wide x 4" deep. The finish shall be baked-on powder coat in Ceiling White color. The units shall be available in ratings from 1500 through 4800 Watts with an optional factory installed single pole thermostat.

The heaters have a low speed 600-RPM motor, which drives a vane axial blower to deliver a quite 175 CFM's of down flow air. The heating element shall be of the block finned type with large, parallel steel fins for quick heat transfer. Unit shall have as standard, a manual reset capillary type limit control, for added safety. Unit weight 22 pounds.



Features & Standard Models

Recess, Surface, Or "T" Bar Mounting



- Fan purge circuit (has 2 wire control circuit for use with remote wall thermostat)
- Disconnect switch
- White powder coated 18 gauge steel grill
- Manual reset thermal limit
- Steel block fin element
- Vane axial fan blade:
1.5KW - 4.0KW units: 700 RPM motor; 175 CFM
4.8KW units: 900 RPM motor; 200 CFM
- Rough in dimensions:
14 3/16" wide x 19 3/16" high x 4" deep
- Grill dimensions:
15 3/8" wide x 20 3/64" high
- Optional factory installed tamper resistant thermostat
- Made in U.S.A.

MFG CATALOG NUMBER	MFG MODEL NUMBER	KW	BTUs	VOLTS	PH	AMPS	TEMP RISE		
03664802	E3383D-RP	1.5	5120	120	1	12.5	27 °F		
03662902	F3386D-RP	4.0	13600	208		19.2	72 °F		
03663002	F3387D-RP	4.8	16382	208		23.1	76 °F		
03663402	HF3384D-RP	2.0 / 1.5	6826/5120	240/208		8.3/7.2	36 °F		
03663502	HF3385D-RP	3.0 / 2.3	10200/7679	240/208		12.5/10.8	54 °F		
03663602	HF3386D-RP	4.0 / 3.0	13600/10200	240/208		16.8/14.4	72 °F		
03663702	H3387D-RP	4.8	16382	240		20	76 °F		
03665002	G3383D-RP	1.5	5120	277		5.4	27 °F		
03664102	G3384D-RP	2.0	6826	277		7.2	36 °F		
03664202	G3385D-RP	3.0	10200	277		10.8	54 °F		
03664302	G3386D-RP	4.0	13600	277		14.4	72 °F		
03664402	G3387D-RP	4.8	16382	277		17.3	76 °F		
International Models									
04708802	M3384D-RPi	1680	5734	220		1	7.6	30 °F	
04708902	M3385D-RPi	2520	8600		11.5		50 °F		
04709002	M3386D-RPi	4032	13761		18.3		72 °F		

Accessories

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	WT. (LBS)	
03778502	BOX3310	Additional Back Can	10	
03811002	3380EX33	Surface Mounting Adapter	1	
04600202	TB3380	2X2 T-Bar Mounting Kit	7	
Thermostat- Add suffix T to model		Factory installed single pole, positive off. Range-60° F-105° F		