



Classic 10

The original, durable standard for portable spot cooling.

The MovinCool Classic 10 portable air conditioner launched the portable cooling industry. It provides 10,000 Btu/h of cooling and takes less than 3.5 sq. ft. of floor space. It's ideal for keeping people cool and productive — and keeping processes working at optimum levels.

Key Features

- No special power requirements. Runs on 115V with 15 amp circuit.
- Minimal electricity use. Consumes just 1.2 kW.
- Generous flexible duct. Lets you target cold air as needed up to 40 ft. from unit.
- Cools in conditions from 70° to 105°F.
- Digital push-button controls for swift and simple operation.
- Ultra-quiet operation — similar to levels of a cat purring.



Ideal for . . .

- Warehouses
- Assembly Lines
- Manufacturing Plants
- Process Cooling
- Construction Sites
- Moisture Removal
- Outdoors and Events

Another line of quality products by DENSO.

DENSO



Classic 10 Specifications

| | | Classic 10 |
|----------------------------|---------------------------------------|------------------|
| Electronic Features | Control Panel | Digital |
| | Thermostat Control | Electronic |
| Cooling Capacity | Rating Conditions: 95°F @ 60% RH | 10,000 Btu/h |
| Electrical Characteristics | Voltage Requirement | 1 Phase, 115 V |
| | Total Power Consumption | 1.1 kW |
| | Current Consumption | 10 amps |
| | Recommended Fuse Size | 15 amps |
| | NEMA Plug Configuration | 5-15 |
| | Min. – Max. Voltage | 105 – 125 V |
| Fans | Motor Output | 0.15 kW |
| Evaporator | Fan Type | Centrifugal |
| | Max. Air Flow | 265 CFM |
| | Max. External Static Pressure | 0.33 IWG |
| Condenser | Fan Type | Centrifugal |
| | Max. Air Flow | 740 CFM |
| | Max. External Static Pressure | 0.13 IWG |
| Compressor | Type | Hermetic Rotary |
| | Output | 0.7 kW |
| Refrigerant | Type / Pre-charged Amount | R-410A / 1.43 lb |
| Dimensions | W x D x H | 19 x 26 x 41 in |
| Net Weight/Shipping Weight | | 156/194 lb |
| Power Cord | Gauge | 14 AWG (3-core) |
| | Length | 10 ft |
| Condensate Tank Capacity | | 5 gal |
| Operating Conditions | Min. – Max. @ 50% RH | 70° – 105°F |
| Max. Duct Length | Per Cold Duct Hose | 40 ft |
| | Hot Duct Hose | 60 ft |
| Max. Sound Level | With Condenser Duct - High/Mid/Low | 55 dB(A) |
| | Without Condenser Duct - High/Mid/Low | 58 dB(A) |

All specifications subject to change without notice. All models come with a standard warranty covering the entire unit and compressor for 12 months. Visit MovinCool.com/warranty for details on MovinCool's industry-best free Extended Warranty Program which includes three (3) years for both parts and labor on portable units.

DENSO Products and Services Americas, Inc.
 3900 Via Oro Avenue | Long Beach CA 90810 USA
 800-264-9573
 MovinCool.com

