



ARCTIC DURASHIELD PLUS

DEPENDABLE, PORTABLE HEAT DUCTING WITH ADDITIONAL ENTRY PROTECTION.

Norseman's Arctic Durashield Plus heat ducting keeps you going in the cold. Its advanced heavy-weight urethane-coated Polyester fabric maintains maximum durability and output, giving you cold-weather performance your crews can count on.

SPECIFICATIONS:





- Manufactured with durable urethane-coated Polyester; water, mold/mildew and fire resistant (FR), and odor-free.
- 500°F (260°C)-rated silicone fabric lead gives additional heat protection at entry.
- Durable FR Santoprene[™] wear strip provides an additional layer of protection.
- Standard colors: Black with yellow wear strip.
- Wire helix provides a strong structure, ensuring consistent airflow.
- Integrated compression straps assist with carrying and ensure compact storage.
- Passes FR testing.



In stock, ready to ship from one of our distribution locations.

Norseman's Arctic Durashield Plus heat duct is *GEAR2PERFORM*.

NORSEMAN, YOUR ONE-STOP SUPPLIER OF *GEAR2PERFORM*.

-  **On-Demand Supply:** Warehousing space and distribution locations across North America.
-  **Exceptional Service:** One-stop supplier of Fabric, Foam and Film Protective solutions.
-  **Superior Quality:** Manufacturing in North America since 1921.
-  **Extensive Experience:** Our Fiercely Reliable[™] team will find a solution to fit your business.

Contact Norseman or your local Sales Representative to order today.



ARCTIC DURASHIELD PLUS

GEAR POINTS: Features specifically designed to ensure Norseman Gear outperforms on your next jobsite.

Deliver warm air where you need it most.



PROTECT

Urethane-coated Polyester with FR Santoprene wear strip and silicone lead for added heat protection.



WITHSTAND

Horizontal or vertical airflow.




FIT

Multiple collar attachments allow for a quick and secure connection.



PERFORM



CONNECTION:

- Various connection methods available, including pin-lock, belted-cuff and wire-ring collar combinations.
- Used in both horizontal and vertical applications.

STANDARD SIZING:

- 12" x 12'
- 16" x 25'
- 12" x 25'



TEMPERATURE RATING:

-60°F to 375°F (-51°C to 190°C)



CUSTOMIZATION:

Custom Options Available

ITEM NUMBER	COLLAR CONFIGURATION	DIAMETER	LENGTH
450955	Pin-Lock / Belted-Cuff Collars	12"	12'
450956	Pin-Lock / Belted-Cuff Collars	12"	25'
450957	Belted-Cuff / Wire-Ring Collars	16"	25'

To learn more about Norseman and our gear, contact one of your local Norseman Sales Representatives or visit our website.

1.800.268.1918
NORSEMANSOLUTIONS.COM