

ZP24K5E-TFD

HFC, R-410A, 60Hz, 3- Phase, 460 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	70.0 / 85.0
Capacity (Btu/hr)	24000	32800
Power (Watts):	2420	1570
Current (Amps):	3.70	2.70
EER (Btu/Wh):	9.90	20.90
Mass Flow (lbs/hr):	353	403
Sound Power (dBA):	69 Avg	74 Max
Vibration (mils(peak-)	2.0 Avg	3.0 Max
Record Date:	2012-12-10	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	1.39
Bore Size(in):	0.00	Displ(ft ³ /hr):	168.92
Stroke(in):	0.00		
Overall Length (in):	9.56	Mounting Length (in):	7.50
Overall Width (in):	9.56	Mounting Width (in):	7.50
Overall Height (in):	12.27	Mounting Height (in):	16.02 *
Suction Size (in):		3/4 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		21	
Initial Oil Charge (oz):		25	
Net Weight (lbs):		47	
Internal Free Volume (in ³):		129.6	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	28.0	MCC (Amps):	8.0	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	16-Dec-2003
LRA Low*:		Max Operating Current:	4.7		
RLA(=MCC/1.4;use for contactor selection):			5.7		
RLA(=MCC/1.56;use for breaker & wire size			5.1		
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-410A HFC	50	3	380/420	Air Conditioning