

Belt Drive and Blower Applications

Features:

- Class B Ins. (Class "A" see notes)
- Continuous Duty
- Energy Efficient \$ (see notes)
- Open and Enclosed
- Reversible
- Sleeve & Ball Bearing
- 60 HZ (50 HZ per notes)



800



ARS2020L

Applications: Centrifugal Pumps, Blowers, Fans

HP	RPM	Volts	Full Load Amps	Service Factor	Frame	Stock Number	Bearings	Protector	Approx. "C"	Dim. "AG"	Enclosure	Notes
1/3	3450	230/115	3.2/6.3	1.35	48Z	F344V1	Ball	Auto	10.3	7.9	Open D.P.	26,341
	1725	115	5.7	1.00	56Z	807L	Sleeve	Auto	7.3	5.8	Open D.P.	260
		115	5.8	1.35	48Z	921L	Ball	None	10.2	8.3	Open D.P.	141
		115	6.2	1.00	56Z	GF2031L	Sleeve	None	9.4	7.8	Open	262
		115	6.8	1.35	48/56	GF2034	Sleeve	Auto	9.4	7.8	Open	92
		230	3.7	1.35	48/56	GF2038	Sleeve	Auto	9.4	7.8	Open	17,92
		115/230	6.4/3.2	1.35	48/56	GF2034D	Sleeve	Auto	8.9	7.3	Open	17,92
		115/230	6.4/3.2	1.35	48/56	BF2034	Ball	Auto	9.4	7.8	Open	17,92,99
		115	6.0	1.15	48	RS2034L	Sleeve	None	9.4	7.8	Open	
		115	4.6	1.00	48	906	Ball	Auto	10.9	9.3	TENV	1
		115	6.0	1.35	48	RB2034	Ball	Auto	9.4	7.5	Open D.P.	
		115	5.9	1.35	48	RB2034L	Ball	None	9.4	7.8	Open D.P.	
		115	5.8	1.35	48Z	922	Ball	Auto	10.3	8.4	Open D.P.	1,91
		115	5.5	1.35	48Z	922L	Ball	Auto	10.2	8.3	Open D.P.	91
		115/208-230	6.2/3.2-3.3	1.35	56Z	BF2034B	Ball	Auto	10.1	7.7	Open	26,307
		115	4.8	1.00	56Z	ARB2034M	Ball	Manual	11.1	9.1	TEAO	26,260
		115/208-230	4.9/2.3-2.5	1.00	48Y	ARB2034L6	Ball	Auto	9.8	8.3	TEAO	26
	115/208-230	5.9/2.8-2.9	1.00	56Z	ARB2034SL	Ball	None	10.0	8.4	TEAO	26,262,307	
	115/208-230	5.0/2.4-2.5	1.00	48Y	ARB2034SLV1	Ball	None	10.4	8.8	TEAO	1,26	
	115/208-230	4.9/2.3-2.5	1.00	48Y	ARB2034L2	Ball	None	9.8	8.3	TEAO	26	
115/208-230	5.9/2.8-2.9	1.35	56Z	ARB2034SV1	Ball	Auto	10.0	8.4	TEAO	26,262,307		
1425	220	3.2	1.35	48	GF2035	Sleeve	Auto	9.4	7.8	Open	269	
1140	115/208-230	6.0/3.0-3.0	1.00	56	ARB2036S	Ball	Auto	11.4	9.5	TEAO	26	
	115/208-230	6.0/3.0-3.0	1.00	56	ARB2036SL	Ball	None	11.4	9.5	TEAO	26	
	115/230	6.2/3.1	1.35	56	RB2036	Ball	Auto	11.1	9.1	Open D.P.	26	

Notes:

- 1. Item to be discontinued when stock is depleted
- 17. Suitable for 208 volts @ 1.0 service factor
- 26. Extended thru bolts, shaft end only
- 91. 5/8" extended thru bolts, 1-7/8" shaft length and 1/2" shaft dia.
- 92. 48/56 FR = 1/2" x 1.5" Shaft with 5/8" shaft adapter - 48/56 slotted 3" height base
- 99. 1/2" extended thru bolts, shaft end
- 141. Shaft diameter is 1/2, N=1.94 with .04 deep flat
- 260. 56Z = 1/2 flatted shaft
- 262. 56Z = 1/2" flat X 1.62 shaft, with 56 FR. Base
- 269. 50 cycle only
- 307. 1/2" shaft, sleeve and key adapter to 5/8" shaft
- 341. 1/2" dia. - shaft 2.25" long

Continues on next page

Shaft Dimensions
 48 = 1/2" Flat x 1-5/8"
 56 = 5/8" Keyed x 1-7/8"

