



FASCO MODEL	TYPE	HP	VOLTS	RPM	SPD.	AMPS	ROT.	BRING.	SHAFT DIM.	"A" DIM.	CROSS REF.	FIG.	NOTES
GREENHECK FAN													
D1061	SP	1/20 - 1/30 - 1/60	115	1500	3	2 - 1.7 - 1.4	CCW	SLV	1/2 X 2-3/4		7108-2425	A	
HEAT N GLOW													
A133	SP	1/50	115	3000	1	1.2					7002-1241	B	
HEATCRAFT													
D1122	PSC	1/16	208-230	1650/1300	1	0.4	CW	SLV	5/16 X 1 5/8	3 5/8	7190-2255, 25308601	C	22
D1123	PSC	1/15	208-230 50/60	1550	1	0.5	CCW	SLV	5/16 X 2 5/8	3 7/8	7190-2285, 25309101	B	1
HEIL-QUAKER													
A064	SP	64CFM	115	3150	1	0.7	CW				610172, 7021-5043	D	
D2810	PSC	1/6	208 - 230	1100	1	1	CCW	SLV	1/2 X 2		HQ 1050892EM, KA55HXHNC-2379	E	
D1071	PSC	1/6	208 - 230	1100	1	0.99	REV	SLV	1/2 X 2-1/8		HQ 1052662EM; 48HXCLW-1562	F	
A148	SP		208 - 230	3000	1	0.5	CCW				HEIL QUAKER, 7021-9237	G	
A151	SP		230	2800	1	0.3	CW				INTER CITY, HQ1050144	H	
HERMAN NELSON													
D829	PSC	1/4	115	825	1	3.8	REV	SLV	1/2 X 2	5 5/8		I	
D880	PSC	1/4	115	1050	1	4.3	CCW	BALL	1 1/2 X 1-1/2	5 1/2		J	
D827	PSC	1/8	115	700	1	2.5	CCW	BALL	1/2 X 2	5 1/2	7-150444-02	J	

NOTES: 1: 4M 370V capacitor 22: 2M 370V Capacitor



FIG. A D1061



FIG. B A133, D1123



FIG. C D1122



FIG. D A064



FIG. E D2810



FIG. F D1071



FIG. G A148




FIG. H A151



FIG. I D829



FIG. J D880, D827



Thermally protected • UL recognized • CSA or ULc certified
NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.