


FASCO Motor Scope Selection Guide



PERMANENT SPLIT CAPACITOR MOTORS - 5" AND 5.6" DIAMETER

FASCO MODEL#	DIA.	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.
D382	5	1/25-1/40-1/50	115	1550	3	.6-4-3	Open Vent.	DS	SLV	6-7/8 X 1/2 X 6-7/8
D277	5	1/10-1/12-1/20	277	1050	3	.7-5-4	Open Vent.	DS	SLV	8-1/2 X 1/2 X 8-1/2
D292	5	1/10-1/15-1/25-1/35	208-230	1050	4	1-7-4-3	Open Vent.	DS	SLV	10-3/4 X 1/2 X 10-3/4
D290	5	1/10-1/15-1/25-1/40	115	1050	4	2.2-1.4-1-.7	Open Vent.	REV	SLV	1/2 X 8-1/2
D291	5	1/10-1/15-1/25-1/40	115	1050	4	2.2-1.4-1-.7	Open Vent.	DS	SLV	10-3/4 X 1/2 X 10-3/4
D294	5	1/10-1/20-1/25-1/35-1/50	115	1050	5	1.3-1-7-.6-5	Open Vent.	DS	SLV	10-3/4 X 3/8 X 10-3/4
D486	5	1/10	115 / 208-230	1550	1	2.5-1.3	Open Vent.	REV	SLV	3/8 X 3-1/8
D347	5	1/8-1/10-1/15-1/20	115	1550	4	2.3-1.6-.7	Open Vent.	DS	SLV	10-1/2 X 1/2 X 10-1/2
D261	5	1/8-1/15	115	1075	2	2.3-1.1	Tot. Encl.	REV	SLV	1/2 X 3
D1050	5	1/8	230	1550	1	1.1	Tot. Encl.	CW	SLV	1/2 X 3
D264	5	1/8	230	1550	1	1.1	Open Vent.	REV	SLV	1/2 X 5
D354	5	1/6-1/10-1/20	115	1050	3	2.8-1.8-1.0	Open Vent.	DS	SLV	8-1/2 X 1/2 X 8-1/2
D221	5	1/6-1/8-1/10-1/12	115	1550	4	3.2-1.7-1.3-1	Open Vent.	DS	SLV	8 X 1/2 X 8
D247	5	1/6-1/8-1/12	230	1550	3	1-7-5	Open Vent.	DS	SLV	8 X 1/2 X 8
D260	5	1/6	115	1075	1	2.9	Tot. Encl.	CW	SLV	1/2 X 3
D258	5	1/5-1/10	208-230	1550	2	2.8-1.3	Open Vent.	DS	SLV	8 X 1/2 X 8
D262	5	1/5	230	925	1	2.3	Open Vent.	REV	SLV	1/2 X 4
D152	5	1/4-1/5-1/6-1/8	277	1050	4	1.6-1.1-9-.7	Open Vent.	REV	SLV	1/2 X 6
D150	5	1/4-1/5-1/6	115	1050	3	4.1-3.2-2.5	Open Vent.	REV	SLV	1/2 X 6
D151	5	1/4-1/5-1/6	230	1050	3	1.7-1.2-1.0	Open Vent.	REV	SLV	1/2 X 6
D245	5	1/3-1/5	230	1050	2	2.9-1.7	Open Vent.	DS	SLV	8 X 1/2 X 8
D1025	5	1/3	208-230	1625	1	2.3	Open Vent.	DS	SLV	7-1/8 X 1/2 X 7-1/4
D488	5.1	1/20	115 / 208-230	1550	1	1.2-6	Open Vent.	REV	SLV	3/8 X 3-1/3
D489	5.1	1/15	115 / 208-230	1550	1	1.2-6	Open Vent.	REV	SLV	3/8 X 3-1/3
D1005	5.1	1/10-1/15	460	1075	2	.5-3	Open Vent.	DS	SLV	9-5/8 X 1/2 X 9-5/8
D487	5.1	1/10	115 / 208-230	1550	1	2.7-1.4	Open Vent.	REV	SLV	3/8 X 3-1/8
D497	5.1	1/10	115 / 208-230	1050	1	2.0-1.0	Open Vent.	REV	BALL	3/8 X 3-1/8
D474	5.1	1/10	115 / 208-230	1550	1	1.9-1.0	Open Vent.	REV	SLV	3/8 X 3-1/3

3 PHASE - 5.6" DIAMETER

FASCO MODEL#	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.
D2720	3/4	200-230	1140	1	3.0	Open Vent.	REV	BALL	5/8 X 5-7/8 KEYED
D2721	3/4	460	1140	1	1.5	Open Vent.	REV	BALL	5/8 X 5-7/8 KEYED

PERMANENT SPLIT CAPACITOR MOTORS - 5.6" DIAMETER

FASCO MODEL#	HP	VOLTS	RPM	SPD.	AMPS	ENCLOSURE	ROT.	BRNG.	SHAFT DIM.
D750	1/8-1/10-1/12	208-230	1075	3	.9-6-5	Open Vent.	DS	SLV	7-1/2 X 1/2 X 9
D751	1/8-1/10-1/15	115	1075	3	2.3-1.5-1.1	Open Vent.	DS	SLV	7-1/2 X 1/2 X 9
D5459	1/8-1/6	208-230	1075	1	1.0	Tot. Encl.	REV	SLV	1/2 X 6-3/4
D799	1/8	208-230	825	1	0.9	Tot. Encl.	REV	SLV	1/2 X 6
D919	1/8	208-230	1075	1	0.9	Tot. Encl.	REV	SLV	1/2 X 6-1/2
D975	1/6-1/10-1/12	277	1075	3	.9-4-3	Open Vent.	REV	SLV	1/2 X 5-1/2
D928	1/6-1/8-1/10	115	1075	3	2.7-2.1-1.7	Open Vent.	REV	SLV	1/2 X 5-1/4
D754	1/6-1/8-1/10	115	1075	3	2.7-2.1-1.7	Open Vent.	DS	SLV	7-1/2 X 1/2 X 9
D927	1/6-1/8-1/10	208-230	1075	3	1.4-9-5	Open Vent.	REV	SLV	1/2 X 6
D752	1/6-1/8-1/10	208-230	1075	3	1.4-9-5	Open Vent.	DS	SLV	7-1/2 X 1/2 X 9
D3775	1/6-1/8-1/10	230	1350	3	.8-6-5	Tot. Encl.	DS	SLV	7-3/4 X 1/2 X 7-3/4
D3752	1/6-1/8-1/10	230	900	3	1.2-8-6	Tot. Encl.	DS	SLV	7-1/2 X 1/2 X 7-1/2
D979	1/6-1/8-1/10	277	1075	3	.9-7-6	Open Vent.	DS	SLV	7-7/8 X 1/2 X 8-1/4
D733	1/6-1/8	115	1075	2	2.5-1.8	Tot. Encl.	REV	BALL	1/2 X 4-1/2
D905	1/6-1/8	208-230	1075	2	1.2-9	Tot. Encl.	REV	SLV	1/2 X 6-1/2
D736	1/6	115	1625	1	2	Tot. Encl.	REV	BALL	1/2 X 3-1/4
D834	1/6	115	1075	1	2.7	Tot. Encl.	CW	BALL	1/2 X 3
D793	1/6	208-230	825	1	1	Tot. Encl.	REV	BALL	1/2 X 6
D798	1/6	208-230	825	1	1.3	Tot. Encl.	REV	SLV	1/2 X 6