

3.3" DIAMETER



General Purpose Motors

- 115, 230, 240 and 208-240 VAC models
- Thermally protected
- UL recognized
- CSA certified



Fig. A D128, D129, D136



Fig. B D365



Fig. C D120, D121, D126, D127, D181, D190, D532, D603, D609



Fig. D D332



Fig. E D364



Fig. F D514, D515



Fig. G D184



Fig. I D105, D106



Fig. K D111



Fig. H D1134



Fig. J D107




Fig. L D1119

SHADED POLE • OPEN VENTILATION • AIR-OVER

H.P.	Volts	Amps	RPM	Rot.	Model	Fig.	"A" Dim.	Shaft Dim.
1/160	208-240	.5	600	C.C.W.	D107	J	2 ⁵ / ₈	⁵ / ₁₆ x 1
1/125-1/200	115	.4-.3	1500	D.S.	D129*	A	2 ¹ / ₈	3 ¹ / ₄ x ¹ / ₄ x 3 ¹ / ₄
1/90	240	.34	1500	C.C.W.	D1119	L	2 ¹ / ₄	¹ / ₄ x 1 ¹ / ₂
1/70	115	.7	1500	C.W.	D120	C	2 ¹ / ₈	¹ / ₄ x 2 ¹ / ₄
1/70	115	.7	1500	C.C.W.	D121	C	2 ¹ / ₈	¹ / ₄ x 2 ¹ / ₄
1/50-1/65-1/80	115	1.1-8-.6	1300	C.W.	D1134	H	2 ¹ / ₄	¹ / ₄ x 1 ³ / ₄
1/50	115	.9	1500	C.C.W.	D609	C	2 ³ / ₁₆	¹ / ₄ x 2 ³ / ₈
1/50	115	.9	1500	C.W.	D603	C	2 ³ / ₁₆	¹ / ₄ x 2 ³ / ₈
1/40	115	1.1	1500	C.W.	D126	C	2 ¹ / ₂	⁵ / ₁₆ x 2 ¹ / ₄
1/40	115	1.0	1500	C.C.W.	D127	C	2 ¹ / ₂	⁵ / ₁₆ x 2 ¹ / ₄
1/40-1/50-1/80	115	1.3-9-.6	1500	D.S.	D128	A	2 ¹ / ₂	4 x ⁵ / ₁₆ x 4
1/40	230	.60	1500	C.W.	D190	C	2 ¹ / ₂	¹ / ₄ x 2 ¹ / ₄
1/40	115	.9	1550	C.C.W.	D106	I	2 ¹ / ₈	¹ / ₄ x 1 ³ / ₄
1/37	115	.94	1550	C.C.W.	D105	I	2 ¹ / ₈	¹ / ₄ x 1 ¹ / ₂
1/30-1/300	115	1.1-1.5	1550/800	C.C.W.	D111	K	2 ³ / ₄	⁵ / ₁₆ x 3
1/30	115	1.3	1500	D.S.	D136	A	3 ¹ / ₄	2 x ⁵ / ₁₆ x 2
1/30	115	1.3	1500	C.W.	D514	F	2 ³ / ₄	⁵ / ₁₆ x 2 ¹ / ₄
1/30	115	1.3	1500	C.C.W.	D515	F	2 ⁵ / ₈	⁵ / ₁₆ x 2 ¹ / ₄
1/30-1/80	115	1.4-.8	1500	C.W.	D532	C	2 ³ / ₄	⁵ / ₁₆ x 1 ¹ / ₂
1/30-1/40	115	1.3-1.0	1500	C.C.W.	D181	C	2 ⁵ / ₈	⁵ / ₁₆ x 2 ¹ / ₄
1/25-1/65	115	1.5-.8	1500	C.W.	D332	D	3 ¹ / ₄	⁵ / ₁₆ x 2
1/25	115	1.8	1500	D.S.	D364	E	2 ⁷ / ₈	1 ⁷ / ₈ x ⁵ / ₁₆ x 1 ⁷ / ₈
1/25	115	1.8	1500	D.S.	D365†	B	2 ⁷ / ₈	1 ⁷ / ₈ x ⁵ / ₁₆ x 1 ⁷ / ₈
1/25	115	1.2	1500	C.W.	D184*	G	3	⁵ / ₁₆ x 1 ⁷ / ₈

* Closed construction □ Impedance protected † Has hubs for end rings

NOTE: Rotation is determined by looking at shaft end. Shaft length is measured from motor face.



Products on this page are NOT SUITABLE for unattended equipment unless indicated by ► symbol. See inside back cover for additional information.

See pages 48 through 71 for OEM direct replacement models.