

Fig.	Order #	Mfg. #	Diam.	Watts	Volts	RPM	Speeds	F/L Amps	Efficiency	Shaft Diam.	Shaft Length	Rot.	"A" Dim.	Bearing Type	Wt. Lbs.	Each
B	S81-923	65313	3-1/2"	6	115	1550	1	0.40	35.0%	1/4"-20 Thd	1/2"	CWOSE	4"	Slv	3.0	109.00
B	S55-411	65411	3-1/2"	9	115	1550	1	0.55	35.0%	1/4"-20 Thd	1/2"	CWOSE	4"	Slv	3.3	105.00
B	S81-924	65412	3-1/2"	9	115	1550	1	0.55	35.0%	1/4"-20 Thd	1/2"	CCWOSE	4"	Slv	3.3	105.00
C	S81-925	65413	3-1/2"	9	115	1550	1	0.50	35.0%	1/4"-20 Thd	1/2"	CWOSE	4"	Slv	3.3	99.00
B	S81-926	65421	3-1/2"	9	230	1550	1	0.27	35.0%	1/4"-20 Thd	1/2"	CWOSE	4"	Slv	3.3	125.00
D	S81-927	65422	3-1/2"	9	115	1550	1	0.27	35.0%	1/4"-20 Thd	1/2"	CCWOSE	4"	Slv	3.3	125.00
D	S81-928	65811	3-1/2"	16	115	1550	1	1.01	35.0%	1/4"-20 Thd	1/2"	CWOSE	4-1/4"	Slv	4.0	139.00
D	S81-929	65812	3-1/2"	16	115	1550	1	1.02	35.0%	1/4"-20 Thd	1/2"	CCWOSE	4-1/4"	Slv	4.0	139.00
C	S81-930	65813	3-1/2"	16	115	1550	1	1.03	35.0%	1/4"-20 Thd	1/2"	CWOSE	4-1/4"	Slv	4.0	139.00
D	S81-931	65821	3-1/2"	16	230	1550	1	0.50	35.0%	1/4"-20 Thd	1/2"	CWOSE	4-1/4"	Slv	4.0	159.00
D	S81-932	65822	3-1/2"	16	230	1550	1	0.50	35.0%	1/4"-20 Thd	1/2"	CCWOSE	4-1/4"	Slv	4.0	159.00
A	S81-161	65001	3-1/2"	25	115	1500	1	1.10	35.0%	1/4"-20 Thd	1/2"	CWOSE	3-3/8"	Slv	4.9	255.00
A	S81-162	65002	3-1/2"	25	230	1500	1	0.55	35.0%	1/4"-20 Thd	1/2"	CWOSE	3-3/8"	Slv	4.9	245.00
A	S81-163	65020	3-1/2"	35	115	1500	1	1.40	35.0%	1/4"-20 Thd	1/2"	CWOSE	3-3/8"	Slv	4.8	269.00
A	S81-164	65021	3-1/2"	35	230	1500	1	0.70	35.0%	1/4"-20 Thd	1/2"	CWOSE	3-3/8"	Slv	4.8	275.00
E	S81-165	65040	3-1/2"	50	115	1500	1	1.70	35.0%	3/8"	1-1/2"	CWOSE	3-5/8"	Slv	7.0	265.00
F	S81-166	65041	3-1/2"	50	230	1500	1	0.85	35.0%	3/8"	1-1/2"	CWOSE	3-5/8"	Slv	7.0	275.00



RESCUE® ECM Watt Motors

Applications:

- For refrigeration evaporator and condensing applications

Features:

- 2-year warranty
- Environmental protection rating: IP67, capable of being submerged in water up to 30 minutes and dust tight

- High efficiency up to 70%

Specifications:

- Straight two prong plug included
- Universal mounting: two sets of feet and five holes in opposite shaft side
- Temperature rating: -40°C +55°C
- Totally enclosed air over (TEAO)
- Thermally protected

Order #	Mfg. #	Watts	Volts	RPM	Speeds	F/L Amps	Efficiency	Shaft Diam.	Shaft Length	Rot.	Bearing Type	Wt. Lbs.	Each
S59-633	EC5411E	4-25	115/230	1550-1725	1	0.2-0.75	70.00%	1/4 x 20THD	0.425"	CWOSE	Ball	2	245.00
S59-632	EC5412E	4-25	115/230	1550-1725	1	0.2-0.75	70.00%	1/4 x 20THD	0.425"	CCWOSE	Ball	2	245.00
S59-643	EC5414E	4-25	115-230	1550-2100	—	0.22-0.75/0.15-0.45	70.00%	1/4"	0.425"	Rev.	Ball	2	315.00



Kryo SSC Unit Bearing ECM Motor

- For use in refrigeration and condensing applications
- Multi-watt range capability
- IP65 certified for applications using pressurized water wash-down

- ATEX certified for applications where flammable refrigerants are used
- Approved for commercial use
- Universal 5-hole mount
- Straight, 2-pin Lyall plug
- Replaces Mars 05620, Nidec EC5411

Order #	Mfg. #	Diam.	Watts	Volts	RPM	F/L Amps	Efficiency	Shaft Diam.	Rot.	Bearing Type	Wt. Lbs.	For Use With	Each
S59-547	5R999	3-2/7"	4-25	115	1550	0.60	66.0%	1/4"	CW	Ball	2.0	Refrigeration Evaporator and Condensing Applications	189.00



Unit Bearing Fan Motors From Morrill

Applications:

- Commercial and domestic refrigeration equipment, room and hood ventilators, room heaters, evaporative coolers and various equipment using 6" to 10" fan blades

Features:

- Cast iron
- Unique two rigid foot bases, top and bottom, with four mounting holes

- Three drilled and tapped holes in base allow vertical or horizontal mounting
- Positive flow lubrication system
- Large pre-oiled felt wick reservoir for long life
- 1/4" x 20" threaded shaft with rubber mounting pad
- S58-707 is a 5W direct replacement for Hill Refrigeration

Order #	Mfg. #	Diam.	Watts	Volts	RPM	Speeds	F/L Amps	Efficiency	Shaft Diam.	Shaft Length	Rot.	Wt. Lbs.	Each
S58-704	10002	3-1/2"	2	115	1550	1	0.16	35.0%	1/4"-20 Thd	1/2"	CWOSE	2.0	85.00
S58-705	10004	3-1/2"	4	115	1550	1	0.32	35.0%	1/4"-20 Thd	1/2"	CWOSE	3.0	95.00
S58-706	10005	3-1/2"	5	115	1550	1	0.34	35.0%	1/4"-20 Thd	1/2"	CWOSE	3.0	95.00
S58-707	10287	3-1/2"	5	115	1550	1	0.34	35.0%	1/4"-20 Thd	1/2"	CWOSE	3.0	115.00
S58-708	10006	3-1/2"	6	115	1550	1	0.36	35.0%	1/4"-20 Thd	1/2"	CWOSE	3.0	99.00
S58-709	10009	3-1/2"	9	115	1550	1	0.53	35.0%	1/4"-20 Thd	1/2"	CWOSE	3.0	99.00
S58-710	10029	3-1/2"	9	230	1550	1	0.27	35.0%	1/4"-20 Thd	1/2"	CWOSE	3.0	105.00