

2510FG2

MANUAL STARTER 277VAC

Product availability: Stock - Normally stocked in distribution facility

Price*: 99.00 USD

Main

Commercial Status	Commercialised
Product or component type	Single Unit Manual Starter
Range of product	F
[In] rated current	16 A
Product certifications	CE CSA UL listed
Cable entry	0.5" and 0.75" knock-outs (top and bottom)
NEMA degree of protection	NEMA 1 plastic standard size
Motor power hp	0.75 hp 230 V DC 0.75 hp 115 V DC 1 hp 277 V AC 1 hp 230 V AC 1 hp 115 V AC
[Ue] rated operational voltage	230 V DC 277 V AC
Poles description	2P
Control type	Toggle switch
Network number of phases	1 phase
Local signalling	No indicator
Reset	Manual
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy

Ordering and shipping details

Category	21101 - 2510,2511,2512 F
Discount Schedule	CP1
GTIN	00785901553953
Nbr. of units in pkg.	3
Package weight(Lbs)	0.79
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will not be Compliant
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------