



Plug in relay, Type KP, tubular, 1 HP at 277 VAC, 10A resistive at 120 VAC, DPDT, 2 NO, 2 NC, 120 VAC coil, pilot light

8501KPR12P14V20

Product availability: Stock - Normally stocked in distribution

facility

Price*: 54.90 USD

I۷	l	a	ı	r
IV	l	a	ı	ı

Product range	8501K
Product type	Relay
Relay Type	General purpose
Mounting type	Socket
Contact composition	DPDT
[Uc] control circuit voltage	120 V AC
Pilot light	Indicator light relay energised LED
Manual operator	Without test button

Complementary

Horsepower rating	1 hp 277 V AC		
	0.33 hp 120 V AC		
Breaking capacity	3 A 120 V AC inductive control circuit UL 508		
	1.5 A 240 V AC inductive control circuit UL 508		
	10 A 277 V AC resistive control circuit UL 508		
	10 A 30 V DC resistive control circuit UL 508		
Maximum switching voltage	300 V AC		
0 0	30 V DC		
Contact material	Silver alloy (AgNi)		
Operating time	20 ms - pick-up		
. 5	20 ms - drop-out		
Shape of pins	Tubular		
For use with	8501NR52		
	8501NR51		

Environment

Ambient temperature range - operational	-40131 °F (-4055 °C)
Product certifications	UL Listed UL Recognized CSA CE
Height	2.66 in (67.56 mm)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	1.4 in (35.56 mm)
Depth	1.4 in (35.56 mm)

Ordering and shipping details

Category	21141-8501 KP
Discount Schedule	CP2
GTIN	785901153726
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.70 in (4.318 cm)
Package 1 Width	1.70 in (4.318 cm)
Package 1 Length	3.00 in (7.62 cm)
Package 1 Weight	3.20 oz (90.718 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	74
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	15.55 lb(US) (7.055 kg)

Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile

Product data sheet

8501KPR12P14V20

Dimensions Drawings

Approximate Dimensions




Product data sheet

8501KPR12P14V20

Connections and Schema

Connections and Wiring Diagrams



Recommended replacement(s)