



Main

Device short name	S
Enclosure type	Open box
Product or component type	Motor starter

Complementary

[In] rated current	18 A
Control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Depth	4.22 in
Electrical connection	Screw clamp terminal
Height	6.77 in
Motor power hp	5 hp 460/575 V AC 3 phases 3 hp 230 V AC 3 phases 3 hp 200 V AC 3 phases
Motor starter type	Non reversing
NEMA size	0
Network number of phases	3 phases
Number of poles	3
Number of thermal units required	3
Permissible voltage	<= 600 V AC
Product weight	5.5 lb(US)
Stage of operation	Common control circuit
Thermal overload type	Melting alloy
Width	4.53 in

Environment

Product certifications	UL listed CSA
------------------------	------------------

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901340904
Nbr. of units in pkg.	1
Package weight(Lbs)	5
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------