Product data sheet Characteristics

8536SCO3V02S

Non-Reversing Starter Size 1, 3-Pole, Thermal - Melting Alloy

Product availability: Stock - Normally stocked in distribution facility

Price*: 557.00 USD

ľ	V	la	Ш	n

IVIAIII	
Commercial Status	Commercialised
Product or component type	Starter
Range of product	S
[In] rated current	27 A
Product certifications	CSA NEMA UL listed
Control circuit	Separate control circuit
Control type	No control units
NEMA degree of protection	Not rated (open device)
Rated power in HP	10 HP 575 V AC 10 HP 460 V AC 7.5 HP 230 V AC 7.5 HP 200 V AC
Poles description	3P
Network number of phases	3 phases
[Ue] rated operational voltage	600 V AC
NEMA size	1
Control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	00785901845119	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.04	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS	Will be Compliant on 3Q2014	
REACh	Reference not containing SVHC above the threshold	

Contractual warranty

Period	18 months