



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	50 VA
Primary voltage	220 x 440 V 240 x 480 V 230 x 460 V
Secondary voltage	115 V 120 V 110 V
Range of product	TF

### Complementary

Network number of phases	1 phase
Rated power in VA	50 VA
Primary voltage	220 x 440 V : 110 V 230 x 460 V : 115 V 240 x 480 V : 120 V
Fuse type	CC 0.41 x 1.50 in top
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Height	4 in
Width	3 in
Depth	3.09 in
Material	Copper winding
Product compatibility	FSC1

### Environment

Product certifications	CSA file LR37055 guide 184-N-90 CE UL listed file E61239
------------------------	--

NEMA degree of protection	Not rated (open device)
Insulation temperature	105 °C

**Offer Sustainability**

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

<b>Product Life Status</b>	<b>END-OF-SALE NOTICE</b>
----------------------------	---------------------------