

Product data sheet

Characteristics

9999SX8

Auxiliary contact, Type S, 1 NO and 1 NC isolated contact, external, field convertible

Product availability : Stock - Normally stocked in distribution facility



Price** : 116.00 USD



Main

Product Range	Type S
Component type	Auxiliary Contact Module
Used with	contactor starter

Complementary

NEMA size	3 4 00 1 6 2 5 7 0
Auxiliary contact composition	1 NO + 1 NC
[Uc] control circuit voltage	<= 600 V AC 50/60 Hz
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 1.5 A 480 V AC inductive control circuit UL 508 10 A <= 600 V AC resistive control circuit UL 508
Height	38.10 mm (1.5 in)
Width	76.20 mm (3 in)
Depth	114.30 mm (4.5 in)
Net weight	0.31 lb(US) (0.14 kg)

Environment

Product certifications	CSA UL recognized
------------------------	----------------------

Ordering and shipping details

Category	21761 - 9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	00785901733539
Package weight(Lbs)	0.14 kg (0.31 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Contractual warranty

Warranty	18 months
----------	-----------