



Main

| | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Range | TeSys |
| Product name | TeSys LRD |
| Product or component type | Differential thermal overload relay |
| Device short name | LRD |
| Relay application | Motor protection |
| Product compatibility | LC1D12 LC1D18 LC1D25 LC1D32 LC1D38 |
| Network type | AC DC |
| Thermal protection adjustment range | 9...13 A |
| [Ui] rated insulation voltage | 600 V power circuit conforming to CSA 600 V power circuit conforming to UL 690 V power circuit conforming to IEC 60947-4-1 |

Complementary

| | |
|----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network frequency | 0...400 Hz |
| Mounting support | Plate with specific accessories Rail with specific accessories Under contactor |
| Tripping threshold | 1.14 +/- 0.06 I _r conforming to IEC 60947-4-1 |
| [I _{th}] conventional free air thermal current | 5 A for signalling circuit |
| Permissible current | 3 A at 120 V AC-15 for signalling circuit 0.22 A at 125 V DC-13 for signalling circuit |
| System Voltage | 690 V AC 0...400 Hz |
| Associated fuse rating | 16 A aM 25 A gG 25 A BS88 |
| [U _{imp}] rated impulse withstand voltage | 6 kV |
| Phase failure sensitivity | Tripping current 130 % of I _r on two phase, the last one at 0 |
| Control type | Red push-button stop Blue push-button for reset mode |
| Temperature compensation | -4...140 °F (-20...60 °C) |
| Connections - terminals | Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible without cable end Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² flexible with cable end Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² solid without cable end Power circuit : screw clamp terminals 1 cable(s) 1.5...10 mm ² flexible without cable end Power circuit : screw clamp terminals 1 cable(s) 1...4 mm ² flexible with cable end Power circuit : screw clamp terminals 1 cable(s) 1...6 mm ² solid without cable end |
| Tightening torque | Control circuit : 1.7 N.m on screw clamp terminals Power circuit : 1.7 N.m on screw clamp terminals |
| Width | 1.77 in (45 mm) |
| Depth | 3 in (76.1 mm) |
| Product weight | 0.32 lb(US) (0.144 kg) |

Environment

| | |
|-------------------------|------------------------------|
| protective treatment | TH conforming to IEC 60068 |
| IP degree of protection | IP20 conforming to IEC 60529 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------|
| ambient air temperature for operation | -4...140 °F (-20...60 °C) without derating conforming to IEC 60947-4-1 |
| ambient air temperature for storage | -76...158 °F (-60...70 °C) |
| mechanical robustness | Shocks 15 Gn for 11 ms IEC 60068-2-7 Vibrations 3 Gn IEC 60068-2-6 |
| dielectric strength | 6 kV at 50 Hz conforming to IEC 60255-5 |
| standards | ATEX D 94/9/CE EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| product certifications | ABS ATEX INERIS CSA UL EAC |

Offer Sustainability

| | |
|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Green Premium product | Green Premium product |
| Compliant - since 1338 - Schneider Electric declaration of conformity | Compliant - since 1338 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Need no specific recycling operations | Need no specific recycling operations |
| WARNING: This product can expose you to chemicals including: | WARNING: This product can expose you to chemicals including: |
| Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. | Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. |
| For more information go to www.p65warnings.ca.gov | For more information go to www.p65warnings.ca.gov |