Table of Contents

PRODUCT GROUP	PAGE #
All Models	
Tools	A-77
Clamps	A-77
RAA/RAB/RCC/RCU/RDU/RDX	
Mounting Hardware	A-77
Accessories	A-77
Powerstar 192/19X	
Gauges/Probes	A-78
Tools/Kits	A-78
Wall Box Rough-ins	A-79
Mounting Brackets	A-79
Competitive Mounting Kits	A-80
Tubing/Tubing Loops	A-81
Restrictors	A-81
Mounting Adapters	A-82
Covers/Finish Plates	A-83
Electrical Finish Plates	A-84
Thermometer Kits	A-85
Replacement Parts	A-86
Service Kits	A-86
832D/DN	
Tools/Kits	A-87
Wall Box Rough-ins	A-87
Covers/Finish Plates	A-87
Replacement Parts	A-88
Service Kits	A-88

Table of Contents (Continued)

PRODUCT GROUP	PAGE #
186	
Wall Box Rough-ins	A-89
Brackets/Clips	A-89
Tubing/Tubing Loops	A-89
Service Kits	A-90
184/188	
Restricters	A-90
Mounting Kits	A-90
Service Kits	A-90
141	
Brackets/Clips	A-91
Service Kits	A-91
Wells	A-91
134	
Brackets/Clips	A-91
Covers/Finish Plates	A-91
356/357	
Tools	A-92
Brackets/Clips	A-92
Mounting Kits	A-92
Wells	A-93
Service Kits	A-93
Enclosure	A-93



		Description	Product Group	Quantity	Part No.
All Models		Calibration Gauge. • 0 to 30 psi (0 to 207 kPa) • Dual scale in psi/kPa • 1% accuracy (ANSI grade 1A) • 2-1/2" (64 mm) dial face • 1/8" NPT bottom connection	All models	1	142-0455
		Calibration Thermometer. 40 to 140°F (4 to 60°C), 1% accuracy with pocket case and clip.	All models	1	141-0573
		Pneumatic Spring Clamp.	All models	1	531-833
RAA-RDX	1111 3333	Mounting Plate.	All models	1	ARG70
		Changeover/Remote Sensor.	RCC, RCU, RDU, and RDX	1	QAH11.1
		Lockable Thermostat Guard	All models	1	141-570

	Description	Product Group	Quantity	Part No.
	Pressure Gauge.1-1/2" diameter 0 to 200 kPa back connected 1/8" NPT male.	19X	1	142-0344
	Pressure Gauge. Dual English/ Metric scale 0 to 30 psig (0 to 200 kPa) compound gauge back connected 1/8" NPT male.	19X	1	142-0373
20 25 30 30 30 30 30 30 30 30 30 30 30 30 30	Pressure Gauge. 0 to 30 psig compound gauge, bottom connected 1/8" NPT male. Replacement or for use with 192-633.	19X	1	142-0426
	Needle Probe. 1-1/2" (38 mm) diameter gauge 0 to 30 psig/ 0 to 200 kPa and calibration cover wrench.	19X	1	192-633
	Needle Probe. (no gauge)	19X	Package of 5	192-759
Process To the second s	Pneumatic Thermostat Calibration Kit. Contains thermometer, gauge squeeze bulb, and fittings for testing room and duct thermostats, pneumatic valve and damper actuators. Includes convenient carrying case. Includes 832-178.	19X	1	832-177
	Calibration Tools. Special tools for calibrating 180, 182, 192 and 832 thermostats. Packed in polyethylene box that fits into carrying case of kit, 832-177.	192	1	832-178
	Test Head Kit. Used for testing 1-pipe transmitters, thermostat air lines for leakage. Packed in polyethylene box that fits into carrying case of kit, 832-177.	192	1	832-179
	Calibration and Cover Screw. Wrench with pocket clip.	19X	Package of 5	192-632

<u> </u>		Description	Product Group	Quantity	Part No.
Powerstar 192/197		Aspirator Box. Required for wall box installation in concrete walls.	19X	1	
wer		• 1- or 2-pipe	19X	1	192-069
ĭ		• 3-pipe			192-502
		Wall Box Rough-In. For 2-pipe dual 1/8" (3 mm) OD copper with plaster plate. 8' (2 m) long, belled to 3/16" (5 m) OD with thermostat chassis plug-in adapters for easy maintenance.	19X	1	192-478
		3-pipe dual 1/8" (3 mm) OD copper with plaster plate. 8' (2 m) long, belled to 3/16" (5 m) OD with thermostat chassis plug-in adapters for easy maintenance.	19X	1	192-498
		Wall Box Rough-In. For 1- or 2-pipe dual 1/4" (6 mm) OD polyethylene with plaster plate. 10' (2 m) long. With thermostat chassis plug-in adapters for easy maintenance.	19X	1	192-480
		3-pipe dual 1/4" (6 mm) OD polyethylene with plaster plate. 8' (2.4 m) long. With thermostat chassis plug-in adapters for easy maintenance.	19X	1	192-499
		Stud Mounting Bracket. 6' (2 m) L. Cut to required length.	192	1	141-098
		Stud Mounting Bracket and Dual Copper Tubing, belled to 3/16" (5 mm) OD with plug-in adapters for easy maintenance.	19X	1	192-482
		Metal/Wood Stud Bracket. Drywall rough-in.	19X	Package of 5	182-683

		Product		
	Description	Group	Quantity	Part No.
	Aspirator Rough-In and Finish Plate Kit. Installed on new or existing walls to conceal controlling instrument.	192	1	192-070
	Universal Kit. Retrofit thermostats including Honeywell, Johnson Controls, and others. Desert Beige (standard). For White, add W to part number.	19X	1	192-300
	Honeywell Kit. Fits Honeywell and others. Desert Beige (standard). For White, add W to part number.	19X	1	192-483
	Johnson Kit. Retrofit to 19X thermostat. Fits Johnson Controls and others. Desert Beige (standard). For White, add W to part number.	19X	1	192-484
	Aspirator Conversion Kit. For 2-pipe thermostat chassis only. Converts existing 18XAP installed aspirator wall box for use with chassis. Kit includes plate, gasket, hardware, and instruction sheet. Order 19X chassis separately.	18XAP to 19X	1	192-648

×		Description	Product Group	Quantity	Part No.
Powerstar 192/19X		3-pipe Copper Tubing. For concrete mason block or hollow walls (stud).	19X	1	192-502
Powers		1- or 2-pipe; split for 3-pipe. Dual 1/4" (6 mm) OD polyethylene with plug-in adapters. 10' (2 m) long.	19X	1	192-600
		1- or 2-pipe. Dual 1/4" (6 mm) OD polyethylene with plug-in adapters. 40' (12 m) long.	19X	1	192-755
		1- or 2-pipe. Dual 5/32" (4 mm) OD polyethylene with plug-in adapters. 40' (12 m) long.	19X	1	192-750
		Preassembled Plastic Tubing Loop. 8" (203 mm) long, with anti-kink spring, plug-in thermostat adapter. Mates to 1/4" (6.4 mm) OD polyethylene tube barbed fitting.	19X	Package of 10	192-481
		Preassembled Plastic Tubing Loop. 8" (203 mm) long, with anti-kink spring, thermostat plug-in adapter. Mates to 5/32" (4 mm) OD polyethylene tubing.	19X	Package of 10	192-505
		Preassembled Plastic Tubing Loop. 8" (203 mm) long, with anti-kink spring. Cut and attach directly to thermostat chassis. Attach compression rings to prevent air leakage. Mates to 1/4" (6 mm) OD polyethylene tubing.	19X	Package of 10	180-896
		20 scim (5 ml/sec) Restrictors. For 1-pipe systems. 1/4" (6 mm) OD polyethylene barb unless noted. Brass coupling, 1/8" NPT.	192 (1-pipe)	1	184-040
	Arra Carlo	20 scim (5 ml/s) In-line Restrictors.	192	Package of 5	184-116
		20 scim (5 ml/s) Restrictor Tee.	192	Package of 5	184-113
	1	External Restrictor Installation Kit. For dual 1-pipe systems. Supply, thermostat and two-controlled devices.	19X	1	184-130

Powerstar 192/19X

	Description	Product Group	Quantity	Part No.
	Adapter Base. 3.38" W x 5.69" H (86 mm W x 18 mm H). • Desert Beige (standard)	19X	1	192-307
	White		1	192-307W
	Adapter Frame. 4.38" W x 5.31" H x 0.09" D (111 mm W x 151 mm H x 2 mm D). • Desert Beige (standard)	19X	1	192-308
	White		1	192-308W
A	Multi-Slotted Plate. Use with	19X	1	192-300
	adapter bases. Not for use with thin profile adapter base.			
	Thin Profile Adapter Base. Measures 3.38" x 4.97" H (86 mm x 126 mm). • Desert Beige (standard)	19X	Package of 5	192-507
	• White		Package of 5	192-507H
11/1	Extra Wall Plate and Mounting Screws. Order only if required for repair or advance mounting prior to factory delivery of chassis (chassis P/N includes wall plate and screws).	19X	1	192-644
SCHOOL AND	Mounting Clips, Spacer and Template for finished drywall.	19X	Package of 10	182-685

	Description	Product Group	Quantity	Part No.
Powerstar 192/19X	Terminal Wall Box Cover Kit. Covers abandoned thermostat locations with blank plate. Dimensions 3.13" x 3.25" (54 mm x 84 mm). • Desert Beige (standard)	19X	1	192-320
	Retrostat Plastic Thermostat Cover Kit. With dial plates that expose or conceal the set point indicator and/or thermometer. Thumb wheel covers to conceal setpoint adjustment. Snap-out tab for Day/Night lever. • Desert Beige (standard) • White	19X 19X	1 1	192-868 192-868W
	Gym Guards. • Desert Beige	19X DN or DNV	1	182-624

		Duaduat		
	Description	Product Group	Quantity	Part No.
W White	Finish Plate. Mounts on 4" x 4" (102 mm x 102 mm) electrical box. Pneumatic thermostat mounts to finish plate. 1/2" (13 mm) diameter hole provided for electrical switch. Stainless steel finish.	19X	1	192-729
- io o	Finish Plate. Mounts on 4" x 4" electrical box. Pneumatic thermostat mounts to finish plate. 1/2" (13 mm) diameter hole provided for electrical switch. Plastic finish in Desert Beige.	19X	1	192-730
	Finish Plate. 1 gang ¹ , 1 room thermostat. ⁴ • Brushed Finish	19X	1	192-860
1/24//	Desert Beige		1	192-861
44 1111	Finish Plate. 2 gang², 1 room thermostat⁴. • Brushed Finish • Desert Beige	19X	1	192-731 192-732
	Finish Plate. 3 gang ³ , 1 room thermostat ⁴ or 3 gang ³ , pneumatic switches ⁴ or 3 gang ³ , 1 room thermostat, 1 pneumatic switch ⁴ .	19X		
	Brushed Finish Desert Beige		1	192-733 192-734
	Finish Plate. 3 gang ³ , 1 pneumatic switch and 1 electric light switch ⁴ or 3 gang ³ , 1 room thermostat, 1 electric light switch ⁴ .	19X		
	Brushed Finish Desert Beige		1 1	192-735 192-736

Ordering Notes

- 1. 1 gang: 3.75" (95 mm) W x 5" (127 mm) H.
- 2. 2 gang: 5" (127 mm) W x 5" (127 mm) H.
- 3. 3 gang: 7" (178 mm) W x 5" (127 mm) H.
- 4. For use with pneumatic or automation room sensors and pneumatic or commercial light switches; comes in brushed, stainless steel finish.

×		Description	Product Group	Quantity	Part No.
Powerstar 192/19X	/50 60 70 80 Model 1 and 2	Thermostat Thermometer Kits. • Scale Range: 45 to 85°F • Use with Model 1 and 2	19X	Package of 5	192-775
	Model 1 and 2	Scale Range: 10 to 30°C Use with Model 1 and 2	19X	Package of 5	192-776
	50 60 70 80	Thermostat Thermometer Kits. • Scale Range: 45 to 85°F • Use with Model 3 and greater	19X	Package of 5	192-786
	Model 3 and greater	Scale Range: 10 to 30°C Use with Model 3 and greater	19X	Package of 5	192-785
	A117)	Setpoint Dials. • Fahrenheit of D.A.	19X	Package of 10	192-779
	-ng 707	Fahrenheit of R.A.	19X	Package of 10	192-780
	109 80 - Right Side	Celsius of D.A.	19X	Package of 10	192-783
	7102	Celsius of R.A.	19X	Package of 10	192-784
	201AC	Fahrenheit of D.A.	19X	Package of 10	192-777
	20140 50-	Fahrenheit of R.A.	19X	Package of 10	192-778
	10,000	Celsius of D.A.	19X	Package of 10	192-781
		Celsius of R.A.	19X	Package of 10	192-782

	Decemention	Product	Overetity	Part No.
	Description	Group	Quantity	
	Replacement Chassis Tube Connector and mounting screws. Also provides access to filters and restrictor plate (10 thermostats).	19X	Material for 10 thermostats	192-525
	Plug-in Adapters for quick thermostat removal. Fits on 5/32" (4 mm) OD polyethylene tubing. Use with compression rings, listed below.			
	Straight, blue	19X	Package of 20	192-485
	Straight, white	19X	Package of 20	192-486
~2×	Plug-in Adapters (Elbow). Blue (provides quick thermostat removal).	19X	Package of 20	192-487
	White (provides quick thermostat removal).	19X	Package of 20	192-488
••	Air Link. Connects adapters for pressure tests.	19X	Package of 20	192-501
	Replacement Cover Screws.	19X	Package of 20	192-536
	Restrictor Plate Replacement Kit. Contains replacement filters, restrictor plates, and gaskets.	19X	Material for 10 thermostats	192-321

		December 1 con	Product	Outsettte	Dowt No.
		Description Adjustment Key. Opens	Group 832 D,	Quantity 1	Part No. 856-055
	(i	Powers cover and changes setpoint.	832 DN	ı	050-055
3	THE STATE OF THE S	Pneumatic Thermostat Calibration Kit. Contains thermometer, gauge squeeze bulb, and fittings for testing room and duct thermostats, pneumatic valve and damper actuators. Includes convenient carrying case. Includes 832-178.	832	1	832-177
		Calibration Tools. Special tools for calibrating 180, 182, 192 and 832 thermostats. Packed in polyethylene box that fits into carrying case of kit, 832-177.	832	1	832-178
		Test Head Kit. Used for testing 1-pipe transmitters, thermostat air lines for leakage. Packed in polyethylene box that fits into carrying case of kit, 832-177.	832	1	832-179
		Wall Box Rough-In. For 2-pipe dual 1/8" (3 mm) OD copper with plaster plate. 8' (2 m) long, belled to 3/16" (5 m) OD with thermostat chassis plug-in adapters for easy maintenance.	832	1	192-478
		"D" Base Kit. for mounting "D" thermostat with exposed tubing. Black base with cutout on top.	832 D, DN	1	832-034
		Gym Guard. No. 1 Silver	832	1	814-018
		"D" Thermostat Friction Knob.	832	1	833-033

832 D/DN

	Description	Product Group	Quantity	Part No.
	"D" Thermostat Replacement Unit. Contains chassis only.	832 D	1	832-040
	Exhaust and Supply Valve Repair Kit. Contains parts for replacement of supply and exhaust valves in one thermostat.	832	1	832-164

	Description	Product	Quantity	Part No.
	Wall Box Rough-In. For 2-pipe dual 1/8" (3 mm) OD copper with plaster plate. 8' (2 m) long, belled to 3/16" (5 m) OD with thermostat chassis plug-in adapters for easy maintenance.	Group 186	1	192-478
	3-pipe dual 1/8" (3 mm) OD copper with plaster plate. 8' (2 m) long, belled to 3/16" (5 m) OD with thermostat chassis plug-in adapters for easy maintenance.	186	1	192-498
	Wall Box Rough-In. For 1- or 2-pipe dual 1/4" (6 mm) OD polyethylene with plaster plate. 10' (2 m) long. With thermostat chassis plug-in adapters for easy maintenance.	186	1	192-480
	3-pipe dual 1/4" (6 mm) OD polyethylene with plaster plate. 8' (2.4 m) long. With thermostat chassis plug-in adapters for easy maintenance.	186	1	192-499
AUTS AUTS AUTS AUTS AUTS AUTS AUTS AUTS	Mounting Clips, Spacer and Template for finished drywall.	186	Package of 10	182-685
	Stud Mounting Bracket and Dual Copper Tubing, belled to 3/16" (5 mm) OD with plug-in adapters for easy maintenance.	186	1	192-482
	Metal/Wood Stud Bracket. Drywall rough-in.	186	Package of 5	182-683
	Dual 1/8" (3 mm) OD Copper Tubing with plug-in adapters. For 1- or 2-pipe. Split for 3-pipe.	186	1	192-479
	Plug-in Adapter with Tee 20 scim restrictor for 1-pipe.	186	Package of 10	192-875

		Description	Product Group	Quantity	Part No.
184/188		20 scim (5 ml/sec) Restrictors. For 1-pipe systems. 1/4" (6 mm) OD polyethylene barb unless noted. Brass coupling, 1/8" NPT.	184	1	184-040
		20 scim (5 ml/s) In-line Restrictors.	184	Package of 5	184-116
		20 scim (5 ml/s) Restrictor Tee.	184	Package of 5	184-113
	Men	Remote Bulb Duct Mounting Kit.	188	1	808-517
		Restrictor Plate Replacement Kit. Restrictor plates and gaskets for 20 scim (5.4 ml/s) restriction Restrictor plates and gaskets for 40 scim (11 ml/s) restriction	188	5 sets of each	188-159

			Product		
		Description	Group	Quantity	Part No.
141	1/200	Remote Bulb Duct Mounting Kit.	141	1	808-517
		Coil Clip.	141	1	356-115
		Capillary Clip.	141	Box of 100	357-001
		Packing Nut Kit. For remote bulb thermostat.	141	1	141-351
		Well. Copper for 141-0520. 4-15/16" (125 mm)	141	1	141-338
		Well. For 141-0521. 2-3/8" (60 mm)	141	1	141-337
	1/200	Remote Bulb Duct Mounting Kit.	134	1	808-517
134	2	Capillary Clip.	134	Box of 100	357-001
		Electric Thermostat Guard. For electric thermostats no larger than 5 1/4" H x 3/4" W x 2" D. (133 mm H x 19 mm W x 51 mm D). Made of cast aluminum. Allen Key included.	134	1	134-117
	POWERS	Concealed Adjustment Faceplate.	134	1	134-034

356/357

		Product		
	Description	Group	Quantity	Part No.
3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Pressure Gauge. 0 to 30 psig (0 to 200 kPa) compound gauge back connected 1/8" NPT male.	356	1	142-0373
10 reserve 20 25 = 25 = 30 s	Pressure Gauge. 0 to 30 psig compound gauge, bottom connected 1/8" NPT male. Replacement or for use with 192-633.	356	1	142-0426
The state of the s	Needle Probe. 1-1/2" (38 mm) diameter gauge 0 to 30 psig (0 to 200 kPa) and calibration cover wrench.	356	1	192-633
	Needle Probe. (no gauge)	356	Package of 5	192-759
	Pipe Plug. 1/8"- 27 NPT	356	1	403-007
	Coil Clip.	357	1	356-115
A	Capillary Clip.	357	Box of 100	357-001
	Swivel Flange Mounting Kit.	356	1	356-090
	Flange Mounting Screws.	356	1	034-289K
	Flange Kit.	356	1	808-412

		Description	Product	Overetites	Dord No.
356/357		Description Copper Well for Rigid Bulbs. 1/2" NPT, 18-7/8" L.	Group 356	Quantity 1	Part No. 358-051
		Copper Well for 357-0003 and 357-0005; Models 1 and 4.	357	1	134-061
	July 2000	Gauge and Tee (back).	356/357	1	142-0425
		Allen Wrench Kit (pack of 5).			192-623
		Lockable Wall Box.			141-570

Notes			

Notes		

