

Powermite 599 Series, MZ Series Zone Control Valves



Description


The Powermite 599 Series ANSI Class 250 MZ Series valve bodies work with any MZ Series electronic actuator with a 7/32-inch (5.5 mm) stroke. Typical applications include control of hot or chilled water or water-glycol solutions up to 50%. Compatible actuators deliver a minimum of 45 lb (200 N) of force.

Features


- Direct-coupled universal bonnet
- Female NPT connections and brass trim
- ANSI Leakage Class IV (0.01% of Cv)

Product Numbers


Use the product numbers in the tables to order the valve and the actuator assembled together. The product number consists of a 3-digit prefix code, a hyphen, and a 5-digit suffix code. The prefix specifies an actuator. The suffix specifies the valve body.




2-Way, Normally Open Valve and Actuator Assemblies with Brass Trim and Female NPT Connections

 Valve Body	Line Size, In. (mm)	Cv (Kvs)	Electro-mechanical, 24V	
			SSB81U 3 pos., fail-in-place	SSB61U 0-10V, fail-in-place
			Actuator Prefix Code	
			254	255
599-01115	1/2 (15)	0.4 (0.34)	254-01115	255-01115
599-01117	1/2 (15)	0.63 (0.54)	254-01117	255-01117
599-01119	1/2 (15)	1 (0.85)	254-01119	255-01119
599-01121	1/2 (15)	1.6 (1.37)	254-01121	255-01121
599-01123	1/2 (15)	2.5 (2.14)	254-01123	255-01123
599-01126	1/2 (15)	4 (3.42)	254-01126	255-01126
599-01129	3/4 (20)	6.3 (5.38)	254-01129	255-01129
599-01131	1 (25)	10 (8.55)	254-01131	255-01131

2-Way, Normally Closed Valve and Actuator Assemblies with Brass Trim and Female NPT Connections

 Valve Body	Line Size, In. (mm)	Cv (Kvs)	Electro-mechanical, 24V	
			SSB81U 3 pos., fail-in-place	SSB61U 0-10V, fail-in-place
			Actuator Prefix Code	
			254	255
599-01100	1/2 (15)	0.4 (0.34)	254-01100	255-01100
599-01102	1/2 (15)	0.63 (0.54)	254-01102	255-01102
599-01104	1/2 (15)	1 (0.85)	254-01104	255-01104
599-01106	1/2 (15)	1.6 (1.37)	254-01106	255-01106
599-01108	1/2 (15)	2.5 (2.14)	254-01108	255-01108
599-01110	1/2 (15)	4 (3.42)	254-01110	255-01110
599-01112	3/4 (20)	6.3 (5.38)	254-01112	255-01112
599-01114	1 (25)	10 (8.55)	254-01114	255-01114

3-Way, Mixing Valve and Actuator Assemblies with Brass Trim and Female NPT Connections

 Valve Body	Line Size, In. (mm)	Cv (Kvs)	Electro-mechanical, 24V	
			SSB81U 3 pos., fail-in-place	SSB61U 0-10V, fail-in-place
			Actuator Prefix Code	
			254	255
599-01132	1/2 (15)	0.4 (0.34)	254-01132	255-01132
599-01133	1/2 (15)	0.63 (0.54)	254-01133	255-01133
599-01134	1/2 (15)	1 (0.85)	254-01134	255-01134
599-01135	1/2 (15)	1.6 (1.37)	254-01135	255-01135
599-01136	1/2 (15)	2.5 (2.14)	254-01136	255-01136
599-01137	1/2 (15)	4 (3.42)	254-01137	255-01137
599-01138	3/4 (20)	6.3 (5.38)	254-01138	255-01138
599-01139	1 (25)	10 (8.55)	254-01139	255-01139

Technical Data


Line Size	1/2 to 1 inch (15 to 25 mm)	Close-off Ratings	According to ANSI/FCI 70-2 See Table 1.
Body	Globe style, UNS CA 844 bronze or forged brass C37700, ANSI Class 250	Controlled Medium:	
Trim	Brass	Two-way valves	Water or water-glycol solutions to 50%
Stem	Stainless steel ASTM A582 Type 303, 7/32-inch (5.5-mm) stroke	Three-way valves	Water or water-glycol solutions to 50%
Seat	Metal-to-metal	Medium Temperature	35°F to 250°F (2°C to 120°C)
Packing	Ethylene propylene O-ring	Max. Differential Pressure for Modulating Service:	
Mounting	NEMA 1 (interior only)	Liquid (2w and 3w)	25 psi (173 kPa)
Flow characteristics:		Rangeability	Cv <1 = >50:1, Cv >1 = >100:1
Two-way valves	Modified equal percentage	Leakage Rate	Class IV (0.01% of Cv)
Three-way valves	Linear		

Table 1. Close-Off Ratings.


Action	Line Size Inches (mm)	Flow Rate, Cv (Kvs)	Close-Off Ratings psi (kPa)	Action	Line Size Inches (mm)	Flow Rate, Cv (Kvs)	Close-Off Ratings psi (kPa)
			Electronic Actuator SSB...				Electronic Actuator SSB...
NC	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	70 (483)	3-Way Mixing, upper	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	70 (483)
	1/2 (15)	2.5 to 4 (2.15 to 3.44)	40 (276)		1/2 (15)	2.5 to 4 (2.15 to 3.44)	40 (276)
	3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	30 (207)		3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	30 (207)
NO	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	60 (412)	3-Way Mixing, lower	1/2 (15)	0.4 to 1.6 (0.34 to 1.37)	25 (172)
	1/2 (15)	2.5 to 4 (2.15 to 3.44)	35 (241)		1/2 (15)	2.5 to 4 (2.15 to 3.44)	15 (103)
	3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	30 (207)		3/4 (20) and 1 (25)	6.3 to 10 (5.43 to 8.6)	10 (69)

Table 2. Valve Dimensions.

2-Way Valve



3-Way Valve



Size In. (mm)	A	B	C	Weight lbs. (kg)
1/2 (15)	1-3/8 (35)	2-1/4 (57)	1-5/16 (33)	.96 (.44)
3/4 (20)	1-5/8 (41)	2-3/8 (59)	1-5/16 (33)	1.13 (.51)
1 (25)	1-15/16 (49)	2-3/4 (69)	1-9/16 (39)	1.7 (.77)
1/2 (15)	2-3/4 (69)	2-1/4 (74)	1-5/16 (33)	1.10 (0.5)
3/4 (20)	3-1/4 (83)	3-9/16 (90)	1-5/16 (33)	1.44 (.65)
1 (25)	3-7/8 (98)	3-15/16 (99)	1-9/16 (39)	2.20 (1.0)

Typical Specifications

Automatic control valves shall have NPT threaded type fittings, 1/2-inch through 1-inch (15 mm through 25 mm) sizes, and shall be ANSI rated to withstand the pressures and temperatures encountered. Valves shall have metal-to-metal seats, stainless steel stems, and Ethylene propylene O-ring packing. Valves shall be ANSI Leakage Class IV (0.01% of Cv). Valves shall have a 50:1 rangeability (Cv <1) or better.

All two-way valves shall be provided with equal-percentage contoured throttling plugs. All three-way valves shall be provided with throttling plugs such that the total flow through the valve remains constant (linear) regardless of the valve position.

For complete technical details on two-way valves with union female, angle female, or union male end connections, see *Powermite™ 599 Series, MZ Series Zone Control Unit Two-way Valves Technical Instructions*, Document No. 155-198P25.

Information in this publication is based on current specifications. The company reserves the right to make changes in specifications and models as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners.
 © 2009 Siemens Building Technologies, Inc.