

Powermite 599 ANSI Class 250, MT Series Terminal Unit 3-Way Valves



Description

The Powermite 599 Series ANSI Class 250 MT Series 3-way valve bodies work with any MT Series pneumatic or electronic actuator with a 7/32-inch (5.5 mm) stroke. Typical applications include mixing of hot or chilled water and the control of glycol solutions up to 50%. Compatible actuators deliver a minimum of 67 lb (300 N) of force.

Features

- Direct-coupled universal bonnet.
- Female NPT end connections with brass and stainless steel trim.
- ANSI Leakage Class IV (0.01% of Cv).

Product Numbers

Use the product numbers in the tables to order the valve and the actuator assembled together. The product number consists of a 3-digit prefix code, a hyphen, and a 5-digit suffix code. The prefix specifies an actuator. The suffix specifies the valve body.



















Table 1. 3-Way, Mixing Valve & Actuator Assemblies with Brass Trim.

 Valve Body	Valve Size, Inch	Cv (Kvs)	2-Inch Pneumatic Actuators, Spring Return (Fail Safe) *			Electro-mechanical, 24V						
			10-15 psi (69-103 kPa)	3-8 psi (21-55 kPa)	8-13 psi (55-90 kPa)	SSC81U Floating, NSR	SSC81.5U Floating SR	SSC61U 0-10V, NSR	SSC61.5U 0-10V, SR	SQS65U 0-10V, NSR	SQS65.5U 0-10V, SR	SQS85.53U Floating, SR
												
			Actuator Prefix Code									
			256	257	258	259	260	261	262	264	265	266
599-02064	1/2	0.4 (0.34)	256-02064A	257-02064B	258-02064	259-02064	260-02064	261-02064	262-02064	264-02064	265-02064	266-02064
599-02065	1/2	0.63 (0.54)	256-02065A	257-02065B	258-02065	259-02065	260-02065	261-02065	262-02065	264-02065	265-02065	266-02065
599-02066	1/2	1 (0.85)	256-02066A	257-02066B	258-02066	259-02066	260-02066	261-02066	262-02066	264-02066	265-02066	266-02066
599-02067	1/2	1.6 (1.37)	256-02067A	257-02067B	258-02067	259-02067	260-02067	261-02067	262-02067	264-02067	265-02067	266-02067
599-02068	1/2	2.5 (2.14)	256-02068A	257-02068B	258-02068	259-02068	260-02068	261-02068	262-02068	264-02068	265-02068	266-02068
599-02069	1/2	4 (3.42)	256-02069A	257-02069B	258-02069	259-02069	260-02069	261-02069	262-02069	264-02069	265-02069	266-02069
599-02070	3/4	6.3 (5.38)	256-02070A	257-02070B	258-02070	259-02070	260-02070	261-02070	262-02070	264-02070	265-02070	266-02070
599-02071	1	10 (8.55)	256-02071A	257-02071B	258-02071	259-02071	260-02071	261-02071	262-02071	264-02071	265-02071	266-02071

* Product numbers in gray shading are available as assemblies only.

Table 2. 3-Way, Mixing Valve & Actuator Assemblies with Stainless Steel Trim.

 Valve Body	Valve Size, Inch	Cv (Kvs)	2-Inch Pneumatic Actuators, Spring Return *			Electro-mechanical, 24 Vac								
			10-15 psi (69-103 kPa)	3-8 psi (21-55 kPa)	8-13 psi (55-90 kPa)	SSC81U Floating, NSR	SSC81.5U Floating, SR	SSC61U 0-10V, NSR	SSC61.5U 0-10V, SR	SQS65U 0-10V, NSR	SQS65.5U 0-10V, SR	SQS85.53U Floating, SR		
														
			Actuator Prefix Code											
		256	257	258	259	260	261	262	264	265	266			
599-02072	1/2	0.4 (0.34)	256-02072A	257-02072B	258-02072	259-02072	260-02072	261-02072	262-02072	264-02072	265-02072	266-02072		
599-02073	1/2	0.63 (0.54)	256-02073A	257-02073B	258-02073	259-02073	260-02073	261-02073	262-02073	264-02073	265-02073	266-02073		
599-02074	1/2	1 (0.85)	256-02074A	257-02074B	258-02074	259-02074	260-02074	261-02074	262-02074	264-02074	265-02074	266-02074		
599-02075	1/2	1.6 (1.37)	256-02075A	257-02075B	258-02075	259-02075	260-02075	261-02075	262-02075	264-02075	265-02075	266-02075		
599-02076	1/2	2.5 (2.14)	256-02076A	257-02076B	258-02076	259-02076	260-02076	261-02076	262-02076	264-02076	265-02076	266-02076		
599-02077	1/2	4 (3.42)	256-02077A	257-02077B	258-02077	259-02077	260-02077	261-02077	262-02077	264-02077	265-02077	266-02077		
599-02078	3/4	6.3 (5.38)	256-02078A	257-02078B	258-02078	259-02078	260-02078	261-02078	262-02078	264-02078	265-02078	266-02078		
599-02079	1	10 (8.55)	256-02079A	257-02079B	258-02079	259-02079	260-02079	261-02079	262-02079	264-02079	265-02079	266-02079		

* Product numbers in gray shading are available as assemblies only.

Technical Data

Valve Size	1/2-inch to 1-inch	Controlled Medium	Water, glycol solutions to 50%
Body	Globe style, UNS CA 844 bronze or forged brass C37700, ANSI Class 250	Medium Temperature	35°F to 250°F (2°C to 120°C)
Trim	Brass or Stainless Steel	Maximum Differential Pressure for Modulating Service:	
		Media	Brass
		Liquid	25 psi (173 kPa)
			Stainless Steel
			50 psi (345 kPa)
Seat	Metal-to-metal	Rangeability	Cv <1 = >50:1, Cv >1 = >100:1
Packing	Ethylene propylene O-ring	Leakage Rate	Class IV (0.01% of Cv)
Spring Range	8 to 13 psi (55 to 90 kPa)	Flow Characteristics	Linear
Close-off Ratings	According to ANSI/FCI 70-2 See Table 3.	Mounting	NEMA 1 (interior only)

Table 3. Close-Off Ratings in psi (kPa).

Action	Valve Size Inch	Flow Rate, Cv (Kvs)	Electronic Actuator		Close-Off Ratings @ 20 psi (138 kPa)		
			SQS	SSC	2-Inch Pneumatic Actuator		
					3-8 psi (69-103 kPa)	8-13 psi (21-55 kPa)	10-15 psi (55-90 kPa)
3-way, upper	1/2	0.4 to 1.6 (0.34 to 1.37)	95 (655)	95 (655)	40 (276)	95 (655)	120 (828)
	1/2	2.5 to 4 (2.15 to 3.44)	50 (345)	50 (345)	28 (193)	50 (345)	65 (448)
	3/4 and 1	6.3 to 10 (5.43 to 8.6)	40 (276)	40 (276)	18 (124)	40 (276)	50 (345)
3-way, lower	1/2	0.4 to 1.6 (0.34 to 1.37)	160 (1103)	95 (655)	95 (655)	45 (310)	20 (138)
	1/2	2.5 to 4 (2.15 to 3.44)	85 (586)	55 (379)	45 (310)	25 (172)	15 (103)
	3/4 and 1	6.3 to 10 (5.43 to 8.6)	70 (482)	40 (276)	35 (241)	10 (69)	—




Figure 1. 3-way Valve Dimensions in Inches (mm).

Valve Size Inch	A	B	C	Weight lbs (kg)
1/2	2-3/4 (70)	2-15/16 (74)	1-5/16 (33)	1.10 (0.5)
3/4	3-1/4 (83)	3-9/16 (90)	1-5/16 (33)	1.44 (.65)
1	3-7/8 (98)	3-15/16 (99)	1-9/16 (39)	2.20 (1.0)

Typical Specifications

Automatic control valves shall have NPT threaded type fittings, 1/2-inch through 1-inch sizes, and shall be ANSI rated to withstand the pressures and temperatures encountered.

Valves shall have metal-to-metal seats, stainless steel stems, and Ethylene propylene O-ring packing.

Valve shall be ANSI Leakage Class IV (0.01% of Cv). Valves shall have >50:1 rangeability for Cv <1 and >100:1 rangeability for Cv >1.

All three-way valves shall be provided with throttling plugs such that the total flow through the valve remains constant (linear) regardless of the valve position.

For complete technical details on valves with stainless steel trim, see *Powermite 599 Series, MT Series Terminal Unit Three-way Valves Technical Instructions, 155-197P25*.

Information in this publication is based on current specifications. The company reserves the right to make changes in specifications and models as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners. © 2007 Siemens Industry, Inc.