

CHPR25 SERIES

PLENUM-RATED UNIT HEATER (CONCEALED SPACE USE – ZERO CLEARANCE)



IDEAL SPACES

- Between finished ceiling and drop ceiling
- Plenum space
- Freeze Protection

COLORS

- Neutral Gray

DIMENSIONS

- 14" L x 12-1/2" H x 14" D

TEMP RANGE

- 40°–90°F

CFM

- 150



- Plenum-rated approved for installations in concealed spaces (between finished ceiling and drop ceiling, plenum space, or inside a plenum). It may be installed in areas that are not readily accessible and may be installed for freeze protection
- 18-gauge all steel casing with polyester powder coat finish for corrosion protection
- Steel finned low-watt density element. High limit thermal cutout automatically shuts off current in event of overheating and reactivates the heater when temperature returns to normal
- Fan delay control. feature allows only warm air to be distributed; optional alarm (240V) to alert automatic thermal limit tripped (Model AFL240)
- Built-in thermostat
- Control box gasket to keep out moisture and dust; NEMA 12 construction
- Fan motor completely enclosed, permanently lubricated and thermally protected
- Single point field wiring connection for easy installation and maintenance



www.qmarkmep.com

For Technical Services, Call 800-642-4328

ITEM# QFLY_CHPR25_1217-1



CHPR25 SERIES

PLENUM-RATED UNIT HEATER (CONCEALED SPACE USE – ZERO CLEARANCE)

MODELS & SPECIFICATIONS

| CATALOG NO. | UPC NUMBER | VOLTS | HZ | KW | PHASE | BTU/HR | FPM | RISE | SHIP AMPS | SHIP WT. (LBS) |
|-------------|-----------------|-------|-------|-----|-------|--------|------|------|-----------|----------------|
| CHPR25 | 6 85360 14954 7 | 240 | 50/60 | 2.5 | 1 | 8530 | 1880 | 60°F | 10.7 | 26 |
| | | 208 | 50/60 | 1.9 | | 6398 | | 46°F | 9.42 | |

ACCESSORIES

| CATALOG NO. | UPC | DESCRIPTION | SHIP WT. (LBS) |
|-------------|----------------|---------------------|----------------|
| AFL240 | 6 8536015347 6 | Thermal Limit Alarm | 1 |

