


# PRODUCT SUBMITTAL SHEET



Capacities
5kW and 10kW 208, 240, or 480V 3 Phase (Field Convertible to 1 phase) Thermostat Range: 40° - 90° F Air Movement: 500 CFM MAX

## CUS SERIES CABINET UNIT HEATERS



Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Architect: \_\_\_\_\_

Engineer: \_\_\_\_\_

Contractor: \_\_\_\_\_

Submitted By: \_\_\_\_\_

Date: \_\_\_\_\_

Submitted By:		Date:	
Approved By:		Date:	

Item	QTY	Catalog Number	Tag	Watts	Volts	PH	AMPS	Weight

ACCESSORIES			
Item	QTY	Part Number	Tag



470 Beauty Spot Road East  
Bennettsville, South Carolina 29512  
www.marlymep.com

**Stock Cabinet Unit Heaters: Stock Models and Specifications**

CATALOG NUMBER	UPC	CFM HI	CFM LOW	DIM	WT	VOLTS/PH	WATTAGE/kW
CUS93505203FFW	00685360174051	250	200		120 lbs.	208V/1-3Ø	5
CUS93505203FFWD	00685360174068	250	200	35" W	120 lbs.	208V/1-3Ø	5
CUS93505243FFW	00685360174075	250	200	26 3/8" H	120 lbs.	240V/1-3Ø	5
CUS93505243FFWD	00685360174082	250	200	9 7/8" D	120 lbs.	240V/1-3Ø	5
CUS93505483FFW	00685360174099	250	200		120 lbs.	480V/1-3Ø	5
CUS93505483FFWD	00685360174105	250	200		120 lbs.	480V/1-3Ø	5
CUS94510203FFW	00685360174112	500	400		120 lbs.	208V/1-3Ø	10
CUS94510203FFWD	00685360174129	500	400	45" W	120 lbs.	208V/1-3Ø	10
CUS94510243FFW	00685360174136	500	400	26 3/8" H	120 lbs.	240V/1-3Ø	10
CUS94510243FFWD	00685360174143	500	400	9 7/8" D	120 lbs.	240V/1-3Ø	10
CUS94510483FFW	00685360174150	500	400		120 lbs.	480V/1-3Ø	10
CUS94510483FFWD	00685360174167	500	400		120 lbs.	480V/1-3Ø	10

\*NOTE: All units are wired as 3 phase but are field convertible to 1 phase if needed

ACCESSORIES				
CATALOG NO.	DESCRIPTION	COMPATIBLE WITH	FUNCTION	SHIP WT. (LBS)
CUH935RTK	Ceiling or Wall Recess Trim Kit	CUH935	Provides a neat finish to semi-recessed or full recessed application.	3
CUH945RTK		CUH945		4
CUH935BK	Floor/Toe-Space Base Kit	CUH935	16 gauge, muted black base is recessed from the heater front and sides to provide an attractive and practical floor mounting application.	9
CUH945BK		CUH945		10
CUH935WF	Permanent, Reusable Washable Filter	CUH935	Replaces standard filter Washable filter can be cleaned and replaced.	4
CUH945WF		CUH945		6

FACTORY-INSTALLED ACCESSORIES - FFW MODELS		
ACCESSORY	DESCRIPTION	
BUILT-IN THERMOSTAT	Standard	Built-in single stage thermostat with adjustable knob to have heater run until demand is satisfied.
MANUAL RESET	Standard	Manual Reset over temperature cutout wired into control circuit. Supplied in addition to auto-reset cutout.
DEAD FRONT DISCONNECT SWITCH	Standard	A three pole non-fused disconnect switch disconnects power to the heater. Design prevents entry into the control compartment until disconnect switch is turned to the OFF position.

FACTORY-INSTALLED ACCESSORIES - FFW MODELS		
ACCESSORY	DESCRIPTION	
SMARTSERIES® PLUS	Standard	Built-in two stage thermostat runs 2/3 elements on stage 1 and full heat for stage 2. Fan cycles on high speed only. Comes with BACnet BMS compatibility, scheduling, cooling mode (Fan-Only), and keypad lock.
MANUAL RESET	Standard	Manual Reset over temperature cutout wired into control circuit. Supplied in addition to auto-reset cutout.
DEAD FRONT DISCONNECT SWITCH	Standard	A three pole non-fused disconnect switch disconnects power to the heater. Design prevents entry into the control compartment until disconnect switch is turned to the OFF position.