

Flexi Frame

PRODUCT

Flexi Frame for modular AC systems

PURPOSE

For mini-split and VRF applications designed to provide stability and spread loads evenly across flat roof surface.

FEATURES

- Finish: 1.6-inch square galvanized steel beams and crossbars
- Feet: 12.6-inch square polypropylene design with integral rubber mat
- Legs: 1.9-inch diameter steel tube with M24 stud adjuster and thick U-clevis



FF-BF-B



FF-BF-B & FF-EF-B

ITEM NO.	DESCRIPTION	LENGTH	WIDTH	MIN HEIGHT	MAX HEIGHT	SAFE WORKING LOAD	QTY OF FEET
FF-BF-B	Flexi Frame Base Stand	47.25 in.	47.25 in.	12 in.	16 in.	1,100 lbs.	4
FF-EF-B	Flexi Frame Extender Stand	47.25 in.	47.25 in.	12 in.	16 in.	1,100 lbs.	2
FF-BF-1500-B	Flexi Frame 1500 Base Stand	59.10 in.	59.10 in.	12 in.	16 in.	1,100 lbs.	4
FF-EF-1500-B	Flexi Frame 1500 Ext Stand	59.10 in.	59.10 in.	12 in.	16 in.	1,100 lbs.	2

Operating Temperatures: -13° F to 176° F