

SPARK IGNITORS



62-23556-03 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-23556-03	1-15/16	1-1/8	90	1-1/4	90	5/32	96	Cut wire (for use with nail pin)



62-23556-04 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-23556-04	1-15/16	1-1/8	90	1-1/4	90	5/32	40	Cut wire (for use with nail pin)



62-23556-08 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-23556-08	2-3/16	1-1/8	90	1-1/4	90	5/32	96	Cut wire (for use with nail pin)



62-23556-10 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-23556-10	2-3/16	1-1/8	90	1-1/4	90	5/32	111	Cut wire (for use with nail pin)



62-23556-11 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-23556-11	1-7/8	1-1/8	90	1-1/4	90	5/32	40	Cut wire (for use with nail pin)



62-23556-82 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-23556-82	1-15/16	1-1/8	90	1-1/4	90	5/32	35	1/4 inch Quick Connect



62-24141-02 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-24141-02	1-1/2	3/4	116	5/8	90	1/8	27	0.084 in. dia.round pin term.



62-24141-04 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-24141-04	1-15/16	1-3/16	78	3/4	90	1/8	40	0.084 in. dia.round pin term.



62-24141-05 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-24141-05	1-15/16	1-3/16	78	3/4	90	1/8	40	1/4 inch Quick Connect



62-24164-01 Direct Spark Ignitor (DSI)

PART NO	LENGTH MNTNG FLANGE TO IGNITOR TIP (IN)	LENGTH SPARK ELECTRODE OFFSET (IN)	ANGLE SPARK ELECTRODE OFFSET (IN)	LENGTH GROUND ELECTRODE OFFSET (DEGREES)	ANGLE GROUND ELECTRODE OFFSET (DEGREES)	SPARK GAP (IN)	WIRE LENGTH (IN)	TERMINATION
62-24164-01	2-1/8	1-3/16	83	13/16	135	1/8	35	0.084 in. dia.round pin term.