

# SURE FLAME

SOLD EXCLUSIVELY BY **heat wagon**

# IX 1500

DUAL FUEL/INDIRECT  
1,500,000 BTU



## IX1500 1,500,000 BTU / Hr



### Features:



- Quick change fuel supply.
- **Patented Sure Flame engineered burner & exchanger.**
- Compact Design - uses less space on the jobsite and during the off season.
- 3 safety shut down controls (High limit switch, air switch and flame rod).
- Forklift accessible side and ends.
- Three power configuration options.
- 24 x 24" square outlet (standard).
- 24" single round outlet (optional).
- 2 x 20" round outlets (optional).
- Recirculation feature.
- Remote thermostat / standard equipment.
- 3 Year Warranty <sup>‡</sup>

### Specifications

Heat Input	Heater Efficiency	Approx. Fuel Consumption		Fan Rating	Heat Rise	Motor Power	Dimensions (LxWxH)		
1,500,000 BTU / Hr	80%	62 L / Hr 69.2 Lbs / Hr (propane) 1500 CFH (natural gas)		18,000 CFM*	95°C	208/230/460 & 575 V	124.5" x 32.5" x 77.5"		
Max Amp Load	3 Ph / 208/230/460 V	3 Ph / 575 V	Inlet Diameter	Outlet Diameter	Max Duct Length	Flue Diameter	Weight	Gas Connection	Gas Supply Pressure
40/36/18 A		14.4 A	24" x 24" Sq	24" x 24" Sq	400'	12"	2160 Lb	1-1/2" NPT	1/2 to 5 PSI

\*Advertised CFM is the fan rating, not the output CFM. Actual CFM output will vary depending on operating conditions. <sup>‡</sup>See [sureflame.ca/warranty](http://sureflame.ca/warranty) for coverage.

**heat wagon**

342 N. 400 E. Valparaiso, IN 46383  
219-464-8818 • 219-462-7985 • [www.heatwagon.com](http://www.heatwagon.com)