

HV SERIES

These high velocity blowers provide powerful airflow that is strong enough to stand up to any industrial setting, such as manufacturing facilities or warehouses. Additional mounting options are available.



MODELS	BLADE SIZE	TYPE	MOTOR HP	VOLTS	CFM	COVERAGE AREA SQ. FT.	AMPS
HV18-120V	16"	Direct Drive	1/2	120	5,000	175	3.4
HV24-120V	22"				8,500	275	3.8
HV30-120V	28"		1		14,250	375	7.6

ACCESSORIES	
MODELS	TYPE (Fits Model)
HV-1	Dock Arm (HV 18 ONLY)
HV-2	Wall/Column (HV 18/24)
HV-3	Wall/Column (Fits All)

FEATURES

- ▶ Heavy-duty yoke mounting bracket design with 2" square steel tubing frame
- ▶ Aluminum 3-paddle blade system with steel hub and cast aluminum spider connections
- ▶ Single speed fan motor - hard wired (no cord)
- ▶ TEAO motor has a Class B rating, with automatic thermal protection & ball bearing design for harsh environments
- ▶ Front & rear spiral wound grills are OSHA approved & have a black powder coated finish
- ▶ Fan design provides (9) adjustment settings at 15° variations ; supplied mounting brackets allow for 120° pivot
- ▶ Voltage options 120V, 208/240V, 277V, 480V
- ▶ Fan ships fully assembled
- ▶ ETL listed & meets OSHA standards

MOUNTING ACCESSORIES



HV-1



HV-2 ; 22" reach
HV-3 ; 25" reach



HV Stand
(low, medium & high)

** Stand option also available

