

Relays

Time Delay Relays For AC & HP Applications

- For A/C and HP applications in Trane air handlers
- UL Approved horsepower: 3/4 hp
- Pilot duty pole minimum: 3VA at 24VAC, maximum: 25V at 24VA
- Input: 24VAC nominal
- Total power consumption: 0.5VA (relay de-energized), 4.0VA (relay energized)



Part #	Mfg #	Contact Ratings	FLA	RLA	Resistive
RLY02807	57T01-001B1	25VA @24VAC Power/Pilot Pole, 2-Sec On-Delay	7A	36A	Includes PC Board
RLY03081	57T02-001B1	25VA @24VAC Power/Pilot Pole, 2-Sec On/45-Sec Off Delay	7A	36A	Includes PC Board

Time Delay Relay



Part #	Mfg #	Description
RLY03167	D155079P01	Time Delay Relay

Delay Timers

ICM205 Delay On Break Timer

- 4-Terminal
- Brownout protection
- Compressor lockout/anti-short cycle timer
- Helps prevent scroll compressor reversal
- Input:
 - Voltage: 18 to 30VAC
 - 1.5A
 - 15A Inrush
 - Time delay: 5-minute fixed
- UL 873 Recognized as compressor controller



Part #	Mfg #	Description
TMR00163	ICM205	5 Minute Timer

