



THE CMB

- Belt drive
- Yoke mount
- Tilts up/down 90° and swivels 360°
- Automatic belt tensioner
- Safety cable included

The “CMB” is great for factories, gymnasiums or anywhere there is a need to have precise directional ceiling mounted cooling.

Model	Blade Diameter	CFM	RPM	HP	Amps	Width	Depth	Height	Approximate Weight
CMB3613	36"	12,100	500	1/2	7.5	44"	19"	51"	185
CMB4213	42"	14,445	500	1/2	7.5	51"	19"	56"	195
CMB4214	42"	15,850	505	3/4	13.0	51"	24"	56"	200
CMB4815	48"	19,460	475	1	11.0	57"	24"	63"	271

HAZARDOUS LOCATION MODELS

Hazardous location models are made to order and are non returnable. They come equipped with:

- Motor: Single Speed, Div. 1, Class 1, Group D & Class II, Groups F & G
- Aluminum Blade
- Stationary Motor Mount
- No wiring or switch

Model	Blade Diameter	Phase	HP	Width	Depth	Height	Approximate Weight
CMB3613HL-U	36"	1-Phase	1/2 HP	44"	24"	51"	204
CMB3613HL-X	36"	3-Phase	1/2 HP	44"	24"	51"	200
CMB4213HL-U	42"	1-Phase	1/2 HP	51"	24"	56"	224
CMB4213HL-X	42"	3-Phase	1/2 HP	51"	24"	56"	212
CMB4214HL-U	42"	1-Phase	3/4 HP	51"	24"	56"	243
CMB4214HL-X	42"	3-Phase	3/4 HP	51"	24"	56"	233
CMB4815HL-U	48"	1-Phase	1 HP	57"	24"	63"	327
CMB4815HL-X	48"	3-Phase	1 HP	57"	24"	63"	317

*See page 111 for information on hazardous location models.

