## MINGO

## WL22000VE

19,000 RUNNING WATTS

Rugged Steel Design



•—— B & S Commercial Vanguard Engine ——



Brushless Industrial Genend





—— LED Display –

Hours, RPMs, voltage, and frequency readings automatically cycle on the display.



Load Bars —

Easily verify the load balance on each leg of the generator end.




– Warnings –

The LED will flash if any parameter gets outside of normal range. A warning will also be displayed when it is time for an oil change.



 Receptacle Panel with GFCI protection



SP-186/B PG 1 WL22000VE/A

## **WL22000VE**

· ENGIN	νΕ	
ENGINE BRAND	BRIGGS & STRATTON	
ENGINE MODEL	VANGUARD	
ENGINE STARTER	ELECTRIC	
ENGINE SPEED	3600 RPM	
ENGINE CYLINDERS	V-TWIN	
DISPLACEMENT/TYPE	993 CC / OHV	
FREQUENCY REGULATION <sup>(1)</sup>	+/-1.5%	
LOW OIL PROTECTION	STANDARD	
RECOMMENDED OIL <sup>(2)</sup>	10W-30	
OIL CAPACITY	2.3 QT	
FUEL TANK	15 GAL	
FUEL GAUGE	YES	
FULL LOAD RUN TIME <sup>(3)</sup>	4.5 HOURS	
FUEL CONSUMPTION 100%	GAL/HR 3.28	
75%	2.57	
50%	1.88	
25%	1.43	
0%	0.95	
BATTERY SIZE <sup>(4)</sup>	BCI GROUP 26 500CCA	
NOTES: (1) Steady state frequency regulation. (2) The recommended oil is for		

NOTES: (1) Steady state frequency regulation. (2) The recommended oil is for normal applications. See operator's manual for the recommended oil for your needs. (3) Run time is estimated. (4) Battery not included.

## → OPTIONAL ACCESSORIES →

FOUR-WHEEL DOLLY KIT	WITH FLAT-FREE TIRES
BATTERY	BCI GROUP 26 500 CCA
MAINTENANCE KIT	16200-011

•—— ELECTRICAL ——•		
STARTING WATTS	22,000	
RUNNING WATTS	19,000	
RUNNING AMPS @ 120 VAC	158.3	
RUNNING AMPS @ 240 VAC	79.2	
VOLTAGE REGULATION	AVR +/- 1.5%	
MAIN CIRCUIT BREAKER	(2) 40 AMP, 240V (GFCI)	
BONDED NEUTRAL	YES	
120 VOLT RECEPTACLES	(4) NEMA 5-20 20A (GFCI)	
120/240 VOLT RECEPTACLES	(2) 14-50R 50A (GFCI)	
240 VOLT RECEPTACLE	(1) NEMA L6-30 30A (GFCI)	
YOURGEN METER	STANDARD	

• GENSE	T
MOTOR STARTING (CODE G)	6 HP
DBA @ 7 METERS	79
TOTAL HARMONIC DISTORTION	< 6%
LIFTING EYE <sup>(1)</sup>	STANDARD
4-WHEEL DOLLY KIT	OPTIONAL
INSULLATION	CLASS H
PROTECTIVE ROLL FRAME	1.25" DIA. 14 GA. STEEL
ASSEMBLED IN	USA
EPA APPROVED	YES
CARB APPROVED	NO
CSA APPROVED	NO
UNIT WARRANTY <sup>(2)</sup>	3 YEARS COMMERCIAL

NOTES: (1) Shipping eye shipped loose. (2) For more generator warranty, see operator's manual.

SHIPPING	o
SHIPPING DIMENSIONS (L x W x H)	43.5" x 31" x 37"
SHIP WEIGHT	504 LBS
FREIGHT CLASS	70







28.85"

Specifications are subject to change without notice